

INDUSTRIAL TORQUE WRENCH - BI-SQUARE



The 1¹/₁₆" Bi-square version of the Industrial Torque Wrench was developed specifically with rail track maintenance in mind. The critical need of the rail industry is to reduce the chance of any object being left on the track. Fitting directly onto rail fishplate bolts means that no socket or square drive is required, two components that could potentially be separated from the regular version of the Industrial Torque Wrench.

Other versions of this tool available on request.

2	BI-SQUARE - DUAL SCALE
12026	1 ¹ / ₁₆ " Bi-Square, 300 - 1000 N·m, 200 - 750 lbf·ft

INDUSTRIAL TORQUE WRENCHES - SPLIT



Split Industrials are supplied in two parts for easier transportation and storage, but can be assembled and disassembled in seconds.

2	RATCHET SPLIT ADJUSTABLE - DUAL SCALE
12102	4R, 3/4", 150 - 700 N·m, 100 - 500 lbf·ft
12102.01	4R, 1", 150 - 700 N·m, 100 - 500 lbf·ft
12101	5R, 3/4", 300 - 1000 N·m, 200 - 750 lbf·ft
12101.01	5R, 1", 300 - 1000 N·m, 200 - 750 lbf·ft
12100	6R, 1", 900 - 2000 N·m, 700 - 1500 lbf·ft

ELECTRODE WRENCHES



For torque tightening of carbon electrodes.

Standard torque settings are shown. Other settings are available. The 8" Diameter electrode wrench uses the professional torque handle as the control mechanism. Above 8" the Industrial wrench is used as the control mechanism.

9	LOW RANGE
12506	8" (200mm) 312 N·m
12530	10" (250mm) 542 N·m
12531	12" (300mm) 780 N·m

Other models available on request.

9	HIGH RANGE
12532	14" (350mm) 1140 N·m
12533	16" (400mm) 1300 N·m
12535	18" (450mm) 1500 N·m
12536	20" (500mm) 2000 N·m
12537	22" (550mm) 2370 N·m
12538	24" (600mm) 2370 N·m
12538.HD	24" (600mm) 3200 N·m

